



JASOF 404番 O型圈规格表1
(用于运动、圆筒面固定、平面固定)




旧JASO 编号称呼	编号称呼	公称内径	O型圈尺寸		JIS 编号称呼	
			线径d2	内径d1		
1003	19003	3	1.9±0.07	2.8	P 3	
1004	19004	4		3.8	P 4	
1005	19005	5		4.8	P 5	
1006	19006	6		5.8	P 6	
1007	19007	7		6.8	P 7	
1008	19008	8		7.8	P 8	
1009	19009	9		8.8	P 9	
1010	19010	10		9.8	±0.12	P 10
1011	19011	11.2		11		
1012	19012	12.5		12.3		
1013	19013	13.2		13		
1014	19014	14		13.8		
1015	19015	15		14.8		
1016	19016	16		15.8		
1017	19017	17		16.8		
1018	19018	18		17.8		
1019	19019	19		18.8	±0.15	
1020	19020	20		19.8		
1021	19021	21.2		21		
1022	19022	22.4		22.1		
1023	19023	23.6	23.3			
1025	19025	25	24.7			
1026	19026	26.5	26.2			
1028	19028	28	27.7			
1030	19030	30	29.7			
1031	19031	31.5	31.2			
1033	19033	33.5	33.2			
1035	19035	35.5	35.2			
2010	24010	10	2.4±0.07	9.8	P 10A	
2011	24011	11.2		11	P 11.2	
2012	24012	12.5		12.3	P 12.5	
2013	24013	13.2		13		
2014	24014	14		13.8	±0.12	P 14
2015	24015	15		14.8		P 15
2016	24016	16		15.8		P 16
2017	24017	17		16.8		
2018	24018	18		17.8	P 18	
2019	24019	19		18.8	±0.15	
2020	24020	20		19.8		P 20
2021	24021	21		20.8		P 21
2022	24022	22.4		22.1		
2023	24023	23.6		23.3		
2025	24025	25		24.7		
2026	24026	26.5		26.2		
2028	24028	28		27.7		

JASOF 404番 O型圈规格表2
(用于运动、圆筒面固定、平面固定)



旧JASO 编号称呼	编号称呼	公称内径	O型圈尺寸		JIS 编号称呼		
			线径d2	内径d1			
2030	24030	30.5	2.4 ± 0.07	29.7	±0.15		
2031	24031	31.5		31.2			
2033	24033	33.5		33.2			
2035	24035	35.5		35.2			
2037	24037	37.5		37.2			
2040	24040	40.5		39.7			
2042	24042	42.5		42.2			
2045	24045	45		44.7			
2047	24047	47.5		47.2			
2050	24050	50		49.7			
2053	24053	53		52.6			
2056	24056	56		55.6			
2060	24060	60		59.6			
2063	24063	63		62.6			
2067	24067	67		66.6			
2071	24071	71		70.6	±0.4		
3022	35022	22.4		3.5 ± 0.1	22.1	P 22.4	
3024	35024	24	23.7		±0.15	P 24	
3025	35025	25	24.7			P 25	
3026	35026	26	25.7			P 26	
3028	35028	28	27.7			P 28	
3030	35030	30	29.7			P 30	
3031	35031	31.5	31.2			P 31.5	
3034	35034	34	33.7			P 34	
3035	35035	35.5	35.2			P 35.5	
3038	35038	38	37.7			P 38	
3039	35039	39	38.7			P 39	
3040	35040	40	39.7			P 40	
3042	35042	42	41.7		±0.25	P 42	
3044	35044	44	43.7				P 44
3045	35045	45	44.7				P 45
3048	35048	48	47.7				P48
3050	35050	50	49.7				P 50
3053	35053	53	52.6				
3056	35056	56	55.6				
3060	35060	60	59.6				
3063	35063	63	62.6				
3067	35067	67	66.6				
3071	35071	71	70.6	±0.4			
3075	35075	75	74.6				
3080	35080	80	79.6				
3085	35085	85	84.6				
3090	35090	90	89.6				
3095	35095	95	94.6				
3100	35100	100	99.6				

JASOF 404番 O型圈规格表3
(用于运动、圆筒面固定、平面固定)



旧JASO 编号称呼	编号称呼	公称内径	O型圈尺寸		JIS 编号称呼
			线径d2	内径d1	
3106	35106	106	3.5 ± 0.1	105.6	±0.40
3112	35112	112		111.6	
3118	35118	118		117.6	
3125	35125	125		124.6	
3132	35132	132		131.6	±0.60
3140	35140	140		139.6	
3150	35150	150		149.6	